

# REWOQUAT® CPEM

## Product description

Coco pentaethoxy methyl ammonium metho-sulfate

## Physical properties

1. Appearance (20 °C)	yellow, clear liquid
2. Solids content	min. 98 %
3. Colour (Gardner)	max. 12
4. pH value (1 % in water)	5.0 – 7.0

## Application

REWOQUAT® CPEM is used as antistatic agent in various textile applications. Besides, it is used as cationic emulsifier or co-emulsifier alone or in combination with non-ionic emulsifiers.

## Benefits

REWOQUAT® CPEM is a highly concentrated, liquid cationic antistatic agent. REWOQUAT® CPEM does not contain any flammable solvent. It is strongly substantive, low-foaming and has emulsifying properties. REWOQUAT® CPEM is compatible with non-ionics, amphoteric and other cationics. With anionic surfactants, REWOQUAT® CPEM usually forms soluble ion pairs. The compatibility of REWOQUAT® CPEM with anionic surfactants has to be checked for each particular case.

REWOQUAT® CPEM exhibits good stability versus acids, alkalis, electrolytes and hardness salts in conditions currently encountered in practice. REWOQUAT® CPEM is stable to hydrolysis, has a good heat stability and an outstanding tolerance versus calcium ions.

REWOQUAT® CPEM is clearly soluble in cold and warm water up to concentrations of 20 – 30 %. It is soluble in hydrocarbons and chlorinated hydrocarbons at low concentrations (about 5 to 10 %).

## Dosage/Handling

REWOQUAT® CPEM can be applied from aqueous dilutions by the exhaust method, by dipping, lick rollers or by spraying.

Use of 10 % concentration stock dilutions is recommended.

Dosage depends on the application and specific formulation in use, as well as on the required performance.

## Registration status

The components of REWOQUAT® CPEM are listed in the following chemical inventories:

EINECS, TSCA, DSL, AICS, ECL, BAGT, NEPA and China

### Storage stability

REWOQUAT® CPEM as delivered can be stored in closed drums and containers for 12 months.

REWOQUAT® CPEM is not sensitive to frost, but the product stored at temperatures below 20 °C is highly viscous and has to be slightly heated under stirring for proper handling.

Prolonged storage at temperatures above 40 °C or overheating should be avoided.

### Packaging

200 kg open top steel drums,  
4 x 200 kg = 800 kg per Pallet

### Hazardous goods classification

Information concerning

- classification and labelling according to regulations for transport and for dangerous substances
- protective measures for storage and handling
- measures in case of accidents and fire
- toxicity and ecological effects

is given in our material safety data sheets.

07/2015

### Trademark notice and legal notice

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

(Status: July 2015)

### Evonik Nutrition & Care GmbH

Goldschmidtstr. 100, 45127 Essen, Germany

Phone Europe +49 201 173-2665, Asia +86 21 61191 125, Americas +1 804 727 0700

interface-performance@evonik.com, [www.evonik.com/interface-performance](http://www.evonik.com/interface-performance)